

(ステンレス金網)金網(平織)空間率

Mesh	縦線					横線			網目						
	線形 m/m	S W. G #	1本の断面積 m/m ²	25.4m/m 間の本数	25.4m/m 間の本数の 総断面積 m/m ²	線径 m/m	S W. G #	25.4m/m 間の本数	縦線の目開 m/m	横線の目開 m/m	網目 (空間) 面積 m/m ²	25.4m/m 平方の網 目数	25.5m/m ²	空間率 %	25.5m/m ² の凸数
8	0.61	23	0.292	8	2.33	0.610	23	8	2.56	2.56	6.56	64.00	420.2	6.52	32.00
10	0.61	23	0.292	10	2.92	0.610	23	10	1.93	1.93	3.72	100.00	372.0	57.60	50.00
12	0.56	24	0.244	12	2.92	0.559	24	12	1.55	1.55	2.41	144.00	347.0	54.20	72.00
14	0.51	25	0.202	14	2.82	0.508	25	14	1.30	1.30	1.69	196.00	332.6	51.80	98.00
16	0.46	26	0.163	16	2.60	0.457	26	16	1.13	1.13	1.27	256.00	325.1	50.70	128.00
18	0.42	27	0.135	18	2.43	0.413	27	18	0.99	0.99	1.00	324.00	320.1	49.60	162.00
20	0.42	27	0.135	20	2.70	0.417	27	20	0.85	0.85	0.72	400.00	290.0	45.10	28.00
25	0.38	28	0.111	25	2.70	0.375	28	25	0.64	0.64	0.41	625.00	256.0	39.70	312.00
30	0.32	30	0°C 779	30	2.34	0.315	30	24	0.53	0.74	0.39	720.00	283.6	43を	360.00
35	0.32	30	0.078	35	2.72	0.315	30	26	0.41	0.66	0.27	910.00	246.6	38.20	455.00
40	0.27	32	0.059	40	2.36	0.274	32	28	0.36	0.63	0.23	1,120	255.3	39.50	560.00
45	0.25	33	0°C 505	45	2.27	0.254	33	32	0.31	0.54	0.17	1,440	240.4	37.20	720.00
50	0.25	33	0.051	50	2.52	0.254	33	35	0.25	0.47	0.12	1,750	208.2	32.20	875.00
55	0.23	34	0.042	55	2.32	0.233	34	39	0.23	0.42	0.10	2,145	203.7	31.50	1,072
60	0.22	35	0°C 393	60	2.35	0.220	35	42	0.20	0.38	0.08	2,520	176.4	27.30	1,26
65	0.20	36	0°C325	65	2.11	0.200	36	46	0.19	0.35	0.07	2,990	197.3	30.50	1,495
70	0.19	36	0.029	70	2°C 5	0.193	36	49	0.17	0.33	0.05	3,430	1952.0	28.70	1,715
75	0.17	37	0°C234	75	1.75	0.172	37	53	0.17	0.31	0°C 50	3,975	198.7	30.80	1,987
80	0.16	38	0.021	80	1.66	0.180	37	56	0.16	0.27	0°C 42	4,480	188.1	29.10	1,240
90	0.13	39	0°C 137	90	1.23	0.152	38	63	0.15	0.25	0°C 37	5,670	209.7	32.50	2335.00
100	0.12	40	0°C 117	100	1.17	0.132	39	75	0.13	0.21	0.03	7,500	202.5	31.3	3,750